# UNIFORM STATUTORY DECLARATION FORM FOR THE REGISTRATION OF FITTING DESIGNS

NEW BRUNSWICK NUKAVUT

NOVA SCOTIA YUKON

PRINCE EDWARD ISLAND NORTHWEST TERRITORIES

NEWFOUNDLAND AND CABRADOR

MANUFACTURERS NAME: Swagelok Company		
MANUFACTURERS ADDRESS: 29500 Solon Road, Solon, Ohio	441301104	
PLANT LOCATIONS: Headquarters: 29500 Solon Road, Solon,	Ohio 44130 184 (See 44	
CATEGORY OF FITTINGS TO BE REGISTERED, CIRCLE ON	E CATEGORY ONLY	III.E OF THE STANDARD OF CONSTRUCTO
A Pipe fittings, including couplings, toos, efbows, Ys, plugs, unions, pipe of Flanges: all flanges C Vahres: all line valves D Expension joints, flexible connections, and froce assemblies: all types E Strainers, litters, esperators, and attems trapp F Measuring devices, including pressure gauges, level gauges, eight glass pressure transmitters C Contiled capacity-rated pressure relief devices acceptable as primary over boilers, pressure vasaels, piging and fuelble plugs H Pressure retaining components that do not fall into one of the above cale	seps, or reducers ses, levels, or rer preseurs protection on	ASME B31.1 and ASME B31.3 (for unlisted components)
N Nuclear-components: Class 1 D Cisss 2 D Class 3 D, (Mosting AEC SNOW MANUFACTURERS NAME, TRADEMARK, OR LOGG AS IT WILL	APPEAR ON THE PROPERTY	
Swagelok		PORCES O WALDES O WHOSENT TO CAST O OTHER O DESCRIPTION OTHER
LIST OF SUPPORTING DOCUMENTATION AND IDENTIFICATION OF THE	SEACTUAL (TEMS TO BE RE	USTUDEO.
sponsibility for the quality of the end product de solernity declare the knowledge represents the product for which registration is sought reportative ratings, and identification markings are in accordance with anufacture of these fittings is regulated by a Quality Control Program in part and has been verified by BSI claration conscientiously believing it to be will and knowing that it is	th the herein named stander of which extends to each plan	of construction, pressure ds. I further decision that the 11 where fabrication occurs in whole
		purpose and I make this selemn ct as if made under eath.
o 15th day of Feb AD 2018 Rest	Janie Lithius E THIS dent Perhaps County OFFI	S P A C E SOR T HE
clered before me at 5000 Ohio  18 15h day of Feb AD 2018 Resh  Including Public; (eign) Commits Commits  (Affix Official seet to the right)	dent Perioge County OFFI Public, State of Obio solon Expiren 03/08/2019	purpose and I make this solemn of as if made under eath.
clered before me at	dent Periago County O F F I ( Public, State of Obto salon Expires: 03/06/2019	S P A C E SORITHE
clered before me at 5000 Phi D  Is 15th day of Feb AD 2018 Residually Public; (eign) CAffex Official seal to the right)  This registration must be revalidated after ten	dent Periogo County O F F I ( Public, State of Obto solon Expires: 03/00/2019  Try Authority use (10) years from the date of	S P A C E SOR T HE
clered before me at 5010 Phi D  is 15th day of Feb AD 2018 Resident and Sold Billions  minissioner of Cathe Commis & Restaute Commis  Notary Public; (eign) (Affix Official seel to the right)	dent Periogo County O F F I ( Public, State of Obto salon Expires 03/06/2019  TY Authority use (10) years from the date of PROVINCE OF PRIN	S P A C E SORITHE



Canadian Registration Number Submittal #CH-CHECK-2018 Category C: Swagelok CH Series Check Valves Revised Date: April 24, 2018 Page 1 of 2

### Attachment B. Scope of Registration for Swagelok CH Series Check Valves (Category C)

#### **Product Scope**

This document represents the scope of Swagelok® CH Series Check Valves covered by this submission for CRN approval. These products were designed and evaluated in accordance with ASME B31.1 for unlisted components and ASME B31.3 for unlisted components.

#### Summary Table

Product Pressure Bearing Component	Main Pressure Bearing Material (Standard)	Port Connections and Sizes	Maximum Allowable Working Pressure (psig)		Design Code of	
			@100°F	@Max. Temp	Construction	
CHA BORV	316 SS (ASTM A479)	Tube Fitting 1/8", 1/4", 6MM Female NPT 1/4" Male NPT 1/4" Female ISO 1/4" Male ISO 1/4" Male VCO fitting 1/4" Male VCR fitting 1/4"	6000 psig	4280 psig @ 400°F		
		AN (Army/Navy) fitting 1/4"	5000 psig	3575 psig @ 400°F		
CH4	Body	Alloy 400/405 (UNS N04400/ N04405) (ASTM B164)	Tube Fitting 1/8", 1/4", 6MM	5000 psig	5000 psig @ 300°F	ASME B31.1 (Unlisted Components) and ASME B31.3 (Unlisted Components)
CH8 Body		216.99	Tube Fitting 3/8", 1/2", 8MM, 10MM, 12MM Male NPT 3/8", 1/2" Male ISO 1/2" Male VCO Fitting 1/2"	6000 psig	4280 psig @ 400°F	
			Female NPT 3/8" IS IS PART OF	5300 psig	3789 psig @ 400°F	
	Body		Female ISO 1/2 N 0C 20294. 5 Female NPT 1/2"	4900 psig	3503 psig @ 400°F	
			Female SAE/MS 1/2" Pressure Vossel	4568 psig	4280 psig @ 400°F	
			Male VCR fitting 1/2"	4300 psig	3074 psig @ 400°F	
CH8 Body		Alloy 400/405 (UNS N04400/ N04405) (ASTM B164)	Tube Fitting 3/8", 8MM	5000 psig	5000 psig @ 300°F	
	- APTICA WO		Tube Fitting, 10MM	5000 psig	4215 psig @ 300°F	
	Body		Tube Fitting 1/2"	4400 psig	3652 psig @ 300°F	
			Tube Fitting 12MM	4200 psig	3493 psig @ 300°F	
CH16		316 SS (ASTM A479)	Tube Fitting 3/4" Male NPT 3/4", 1" Male ISO 3/4", 1" Male VCO Fitting 3/4",	5000 psig		
	Body		Tube Fitting, 22MM	4900 psig	3560 psig @ 400°F	
			Tube Fitting 1"	4700 psig		
			Tube Fitting 25MM	4640 psig		



Canadian Registration Number Submittal #CH-CHECK-2018 Category C: Swagelok CH Series Check Valves Revised Date: April 24, 2018 Page 2 of 2

Product Pres Series Bea		Material	Port Connections and Sizes	Maximum Allowable Working Pressure (psig)		Design Code of
	Bearing Component			@100°F	@Max. Temp	Construction
CH16	Body	316 SS (ASTM A479)	Male VCO Fitting, 1"	4700 psig	3120 psig @ 400°F	ASME B31.1 (Unlisted Components) and ASME B31.3 (Unlisted Components)
			Female NPT 3/4" Female ISO 3/4"	4600 psig	3289 psig @ 400°F	
			Female NPT 1" Female ISO 1"	4400 psig	3146 psig @ 400°F	
			Male VCR fitting 3/4"	3700 psig	2645 psig @ 400°F	



#### Typical Product Characteristics:

Additional options that do not affect pressure-temperature ratings may be made available within the scope of this registration. Examples of these would include, but not be limited to, poppet springs, lubricants, and body seal materials.

#### Quality System

The Swagelok Company quality system complies with the requirements of ISO 9001:2015. The Swagelok Company maintains BSI Certificate of Registration Number FM 01729, which applies to all locations listed on the Certificate.

#### Special Ordering Instructions

None

#### References

The following product catalog does not represent the full scope of registration, but rather details some of the most common options.

Check Valves MS-01-176, R11

## Attachment A. Swagelok Manufacturing Locations

This document lists the Swagelok locations where end item or component level manufacturing activities take place.

Swagelok Company	Swagelok Company (Falon 1)
29500 Solon Road	348 Bishop Road
Solon, Ohio 44139	Highland Heights, Ohio 44143
USA	USA
Swagelok Company (Highland)	Swagelok Company (Falon 2)
318 Bishop Road	358 Bishop Road
Highland Heights, Ohio 44143	Highland Heights, Ohio 44143
USA	USA
Swagelok Company (OFC)	Swagelok Company (HPF)
29495 F.A. Lennon Drive	6050 Cochran Road
Solon, Ohio 44139	Solon, Ohio 44139
USA	USA
Swagelok Company (Atlantic)	Swagelok Company (Snow Metal)
26651 Curtiss Wright Parkway	6060 Cochran Road
Willoughby Hills, Ohio 44092	Solon, Ohio 44139
USA	USA
Swagelok Company (Micro) 26653 Curtiss Wright Parkway Willoughby Hills, Ohio 44092 USA	Swagelok Company (Alfred) 29500 Ambina Drive Solon, Ohio 44139
Swagelok Hose Services Company (SHSC)	Swagelok Company (Strongsville)
29900 Solon Industrial Parkway	15400 Foltz Road
Solon, Ohio 44139	Strongsville, Ohio 44119
Swagelok (China) Fluid System Technologies Ltd.	Swagelok Company A.G. (European Technology
Changshu Export Process Zone	Center)
Changshu Economic Development Zone	St. GallerstraBe 84
Changshu, Jiangshu	Lachen, Switzerland 8853
215513 China	Switzerland
Swagelok Limited Tromode IM4 4RA Isle of Man	THIS IS PART OF

Technical Standards & Safety Authority Confere & Pressure Vesseln